

MATERIAL SAFETY DATA SHEET – DP70

SECTION 1 – IDENTIFICATION OF CHEMICAL

Supplier:Danlaid Contracting Pty LtdPhone:(03) 8514 6300

Fax: (03) 8514 6310

Address: 43 DeHavilland Rd, MORDIALLOC, VIC, 3195

Product Name: DP70

Description: One-component moisture curing modified polyurethane based compound. Use: Rollable grade waterproofing membrane and protective coating for construction.

SECTION 2 – HAZARDS IDENTIFICATION

This product is classified as: Non Hazardous according to the criteria of Worksafe Australia.

U.N. Number: None	Dange	erous Goods Class: None	Hazchem Code: N/A	
Risk: Irritant to skin	Poisor	ns Schedule: N/A		
Risk Phases:	R22	Harmful if swallowed		
	R43	May cause sensitisation by	v skin contact	
Safety Phases:	S1/2	Keep locked and out of reach of children		
	S23	Do not breathe vapour or	spray	
	S26	In case of contact with eye	s rinse immediately with plenty of water and contact a doctor	
		or Poisons Information Cer	ntre Australia (13 11 26)	
	S36/37 Wear suitable protective clothing and gloves			
	S45	In case of accident or you t whenever possible)	feel unwell, seek medical advice immediately (show the label	

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredients:				
Chemical Ingredient:	C.A.S. No.:	Concentration:		
Polyurethane prepolymer	-	20-40%		
Non-hazardous ingredients		to 100%		

SECTION 4 – FIRST AID MEASURES

Inhaled:	If effects occur, remove to fresh air. Seek medical attention.		
Skin Contact:	May Cause irritation to skin. Symptoms include redness, itching and pain. May cause dermat		
	Wash contact area with soap and water. A cotton pad soaked in castor oil can be used to		
	remove product from skin.		
Eye contact:	May cause severe irritation and discomfort. Immediately flush eyes with water for at least 15		
	minutes (longer is irritation persists), hold eyelids open. Seek medical assistance immediately.		



Swallowed:

Causes irritation to the gastrointestinal tract. Symptoms may include nausea, vomiting and diarrhoea. A potential aspiration hazard if swallowed. May cause damage to lungs. System may parallel inhalation exposure. **Do not induce vomiting.** If vomiting does occur, keep head below hip to prevent aspiration. Seek immediate medical assistance.

Notes to Physician: Contact Poisons Information Centre Australia (13 11 26)

SECTION 5 - FIRE FIGHTING MEASURES

Flammability:	Non flammable liquid. Combustible as dried film.
Flash Point:	Not determined.
Flammability Limits:	Not determined.
Hazchem Code: N/A.	
Specific Hazards:	Toxic fumes including carbon monoxide may be evolved.
Extinguishing Media:	Extinguish with foam, water spray or fog. Do not use water in a jet. Dry chemical power, carbon
	dioxide, sand or earth may be used for small fires only.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Emergency Procedures:

Prevent fluid from escaping to drains and waterways. Contain leaking packaging in a containment drum. Prevent vapours from building up in confined areas. Ensure drain valves are closed at all times. Clean-up and report any spills immediately.

Methods and Materials for Containment and Clean-Up:

Contain spill using sand, earth vermiculite or other suitable absorbent. Place contaminated absorbent in containment drums for disposal. Personnel involved in clean-up must use recommended personal protective equipment. Dispose of in accordance with Local Regulations.

SECTION 7 – HANDLING & STORAGE

Handling:	This material is combustible. Eliminate all ignition sources. Ensure ventilation is sufficient to		
	prevent a build-up of vapour.		
Storage:	Store in a cool dry place. Product will absorb moisture from the atmosphere. Keep containers		
	closed at all times. Avoid storage of partly used pails. Contamination of drummed product with		
	water may lead to drum rapture.		
Container Advice:	Containers, even those that have been emptied, can contain flammable or explosive vapours.		
	Do not cut, drill, weld or perform similar operations on or near containers.		

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

2

National Exposure Standards:

Isocyanate (as NCO)	0.02mg/m3 sensitiser

<u>STEL</u> 0.07mg/m3



TWA (Time Waited Average):	Maximum average airk working day, for a five	oorne concentration experienced over an eight hour day working week over an entire working life.
STEL (Short Term Exposure Limit):	Average airborne conc exceeded at any time o	entration over a 15 minute period which should not be during a normal eight hour working day.
Exposure Limits:	Not established for pro	oduct or individual components.
Ventilation:	Provide general and/o operations, to control	r local exhaust ventilation, depending on the type of airborne exposures.
Biological Limit Values:	No biological limit allo	wed.
Engineering Controls:	Use only in a well vent exposure below recom	ilated area. Ventilation must be sufficient to maintain mended exposure standards above.
Personal Protective Equipment:		
Respiratory:	If inhalation risk exists, we vapours. This must comply smoking eating drinking	ar a respirator fitted with a cartridge suitable for organic with AS/NZS 1715:1994 STANDARD. Wash hands before
Skin/Body:	Wear impervious protective goggles. Ensure protective	e clothing, including boots, gloves, coveralls, and safety equipment is decontaminated before re-use.
Eyes/Face:	Chemically resistant safety wear a full face shield. Ens aware of the location. Sele be in accordance with the Australian Standards, inclu	y glasses with side shields. If there is a risk of splashing, ure eye wash facilities are available and all workers are ection and use of personal protective equipment should recommendations in one or more of the relevant uding:
	• AS 1336:Recom	mended practises for eye protection in the
	• AS/NI7S 1227.	Industrial environment.
	 AS/NZS 1357. AS/NZS 1715: 	Selection, use and maintenance of respiratory protective devices.
	AS 2161:Indust	rial safety gloves and mittens
		(excluding electrical and medical gloves).
	• AS/NZS 2210:	Occupational protective footwear.

• AS 2919:Industrial clothing.

SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES

Appearance:	Viscous liquid	Odour:	Undetermined
PH:	N/A	Specific Gravity:	1.4
Vapour Pressure:	1.0kPa @ 20 ⁰ C	Vapour Density:	3.5 (Air = 1)
Boiling Point:	>160 ⁰ C	Freezing Point:	> -48 ⁰ C
Solubility (water):	Immiscible	Flash Point, cc:	>160 ⁰ C
Viscosity:	55 – 75 Pa.s	VOC:	0.0g/Litre



SECTION 10 - STABILITY & REACTIVITY

Chemical Stability: Conditions to Avoid: Incompatible Materials: Hazardous Decomposition Products:

Stable under normal conditions of use. Stable under normal conditions of use. Strong alkali, acids, oxidising agents, amines and water A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11 – TOXICOLOGICAL INFORMATION

Specific product data is unavailable - information is based on polyurethane prepolymer.

Acute Oral Toxicity:	Low toxicity – LD50 > 2000mg/kg, Rat aspiration into lungs when swallowed or vomited may cause chemical pneumitis which can be			
	fatal.			
Acute Dermal Toxicity:	Low toxicity – LD50 > 2000mg/kg. Classified harmful under EC criteria,			
	Rabbit.			
Chronic Effects on Humans:	Not available.			
Other Toxic Effects on Humans:	Hazardous in case of skin contact (irritant), of ingestion,			
	of inhalation.			
Special Remarks on Toxicity to Animals:	Not available.			

Special Remarks on Chronic Effects on Humans: Special Remarks on other Toxic Effects on Humans: Not available.

Not available.

SECTION 12 – ECOLOGICAL INFORMATION

Specific product data is not available

Persistence/degradability:

This product can degrade rapidly in air. This substance is expected to be removed in wastewater treatment. Based on data for similar components or estimated data, this product is expected to biodegrade rapidly and be "readily" biodegradable according to OECD guidelines. No information available.

Mobility:

SECTION 13 – DISPOSAL CONSIDERATIONS

Material Disposal:

Part containers can be gelled by mixing in 1 - 2% water. If setting the material with water, provide for the foaming by placing in a bunged/sealed area to prevent foam from escaping to surrounding environment. Care should be taken to ensure compliance with national and local authorities.

4



Container Disposal:

Drain container thoroughly of uncured material or mix a little water into uncured material as described above. Ensure empty packaging is allowed to dry.

SECTION 14 – TRANSPORT INFORMATION

This product is not classified as a dangerous good in Australia Dangerous Goods Code by reference to a specific substance name or generic name or group.

U.N. Number: None.

Dangerous Goods Class: None.

SECTION 15 – REGULATORY INFORMATION

Country/Region:	Australia	Inventory:	AICS
Status:	Listed	Poisons Schedule:	N/C

SECTION 16 – OTHER INFORMATION

Acronyms:			
AICS:	Australian Inventory of Chemical Substances		
CAS Number:	Chemical Abstracts Service Registry Number		
Hazchem Code:	Emergency action code that provides information to emergency services		
IARC:	International Agency for Research on Cancer		
NOHSC:	National Occupational Health and Safety Council		
Contact:	Danlaid Contracting Pty Ltd – (03) 8514 6300		
Date of issue:	29 April, 2010		

Important Note:

Data quoted is typical for the product, but does not constitute a specification, and is based on the most accurate information available at the time of writing. All information contained herein is given in good faith, but is subject to change without notice.

5